

Application

Bollard luminaire with unshielded 360° light distribution. Provided without safety guard and three-ply opal glass for even illumination. Designed for use in the illumination of gardens and residential installations.

Materials

Hand-blown three-ply opal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.5lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
Maximum ambient temperature	70° C
LED module wattage	8.0W
System wattage	14.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	728lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

B79817	Anchorage kit
--------	---------------



Bollard · Unshielded			
	LED	A	B
B77743	8.0W	5 1/2	35 3/4

