

Application

This distinctive and robust luminaire provides light with wide beam distribution on one side for illuminating surfaces or pathways from one side of boundaries. The construction is robust enough for people to sit or stand on. These luminaires are ideal for schools, parks and other public areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Galvanized steel anchorage
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 61.2 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 11.8 W
System wattage 15.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 888 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS Custom finish
MGU Marine grade undercoat
RAL RAL Classic, matte finish

Included (available for pre-shipment)

B79808 Anchorage kit



Urban furniture · Shielded bollard					
	LED	A	B	C	D
B77754	11.8 W	15 3/4	18	4 3/4	9 1/2

