Type:
BEGA Product:
Project:
Modified:

Application
Compact floodlight with mounting canopy and outrigger arm. Designed to illuminate architectural features and signage. Pair with a variety of optical accessories.

Materials
Clear safety glass
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
High temperature silicone gasket
Fully potted waterstopper cable
304 stainless steel outrigger arm
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.2 lbs.

EPA (Effective projection area): 0.5 sq. ft.

Electrical

Operating voltage	120-277 V AC
Minimum start temperature	-30° C
LED module wattage	19.0 W
System wattage	22.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1158 lm
LED service life (L70)	60000 hrs

LED color temperature
☐ 4000K (K4)
☐ 3500K (K35)
☐ 3000K (K3)
☐ 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
☐ Black (BLK)
☐ Silver (SLV)
☐ Natural Bronze (NTB)
☐ CUS:
☐ Bronze (BRZ)
☐ White (WHT)
☐ RAL:

Available options

☐ B70055	Elliptical spread lens
☐ B70756	Glare shield · 180°
☐ CUS	Custom finish
☐ FSC	Fusing
☐ MGU	Marine grade undercoat
☐ NTB	Natural bronze (premium finish)
☐ RAL	RAL Classic, matte finish





Compact floodlight · Wide beam

	LED	β	A	B	C	D
B77757	19.0 W	47°	5 1/2	27 1/2	5 1/2	7 1/2

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026