

Application

In-grade location luminaires. The patented mounting system allows for installation in pre-cored holes such as stone, tile or decks. These luminaires are designed to bear pressure loads up to 4400 lbs. from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

Materials

Clear safety glass with white ceramic coating
Corrosion-resistant 304 grade stainless steel
Fully potted waterstopper cable
High temperature silicone gasket
Stainless steel screw clamps

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 7.4 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	6.3W
System wattage	10.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	125lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:


BEGA Product:

Project:

Modified:

Available options

FSC	Fusing
NSL	Non-skid lens



In-grade luminaire · Location luminaire

	LED	A	B	C
B77814	6.3W	9 ⁵ / ₈	8 ⁷ / ₈	7 ¹ / ₄

