

Application

Ideal as individual luminaires for marking egress and danger areas or in rows for illuminating corridors or passageways in public and private projects.

Materials

Pressed crystal glass with white ceramic coating on one side
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, for interior use only

Weight: 0.9 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	3.3W
System wattage	4.9W
Controllability	Non-Dimming
Color rendering index	Ra > 90
Luminaire lumens	164 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)
- Chrome (.3)

Type:


BEGA Product:

Project:

Modified:

Included (available for pre-shipment)

- B19538
- Small opening wiring box



Wall luminaire · Crystal glass					
		LED	A	B	C
B78047	ADA	3.3W	3 1/2	4	2 1/8