

Application

Bollard luminaire with unshielded 180° light distribution and safety guard designed for use in the illumination of gardens and residential installations. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Hand-blown three-ply opal glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Self-expanding sleeve anchors for pre-cast concrete

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.6lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- Maximum ambient temperature90° C
- LED module wattage3.9W
- System wattage8.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens94 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:
BEGA Product:
Project:
Modified:

- Available options
- CUS Custom finish
 - FSC Fusing
 - MGU Marine grade undercoat
 - RAL RAL Classic, matte finish



Bollard · Unshielded with safety guard · 180°			
	LED	A	B
B84024	3.9W	4 ³ / ₈	28 ³ / ₄

