

Application

Bollard luminaire with unshielded 360° light distribution and safety guard designed for use in the illumination of gardens and residential installations. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Hand-blown three-ply opal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
High temperature silicone gasket
Self-expanding sleeve anchors for pre-cast concrete

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.6lbs.

Electrical

Operating voltage120-277VAC
Minimum start temperature-30° C
Maximum ambient temperature90° C
LED module wattage3.9W
System wattage8.0W
Controllability0-10V dimmable
Color rendering indexRa > 80
Luminaire lumens181 lm
LED service life (L70)60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)Bronze (BRZ)
Silver (SLV)White (WHT)
Natural Bronze (NTB)RAL:
CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUSCustom finish
FSCFusing
MGUMarine grade undercoat
RALRAL Classic, matte finish



Bollard · Unshielded with safety guard · 360°			
	LED	A	B
B84028	3.9W	4 ³ / ₈	28 ³ / ₄

