

Application

A pole-top luminaire with asymmetric, Type IV distribution. Ideal for illuminating pathways, plazas and other pedestrian spaces while adding visual interest.

Materials

- Clear UV-stabilized acrylic diffuser
- A380 aluminum alloy
- 316 grade stainless steel
- High temperature silicone gasket
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 22.0lbs.

EPA (Effective projection area): 1.93 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-20° C
- LED module wattage47.7 W
- System wattage54.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens6392lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|-----|---------------------------|
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| RAL | RAL Classic, matte finish |



Pole-top luminaire · Asymmetric wide beam			
	LED	A	B
B84102	47.7 W	8 ⁵ / ₈	34 ¹ / ₂

