

Application

The design of this in-grade floodlight makes it possible to fully illuminate a vertical surface, from the ground up to the edge of the roof. The lower limit of the light distribution is straight without the usual scallop.

Materials

- Hand-blown crystal glass
- Corrosion-resistant 304 grade stainless steel
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- Silicone optic with excellent high temperature and UV stability
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 18.7 lbs.

Electrical

- Operating voltage120V or 277V AC
- Minimum start temperature-30° C
- LED module wattage24.6 W
- System wattage29.2 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2330 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Natural cast bronze. Time and weather factors will create the natural patina of bronze.

Type:
BEGA Product:
Project:
Modified:

Available options
NTB Natural bronze (premium finish)

Included (available for pre-shipment)
BB84618 Installation housing



In-grade floodlight · Wall washer · Bronze						
	LED	β	A	B	C	D
B84175	24.6 W	20°x91°	11 1/4	13 5/8	4 1/4	2 3/8

