

Application

Compact performance floodlight with mounting canopy for mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability
Composite concentric ring louver
BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.6 lbs.

EPA (Effective projection area): 0.43 sq. ft.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	61.7 W
System wattage	68.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	4229 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:


Available options

B71123	Elliptical Spread Lens (Not compatible with internal louver)
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Available accessories

B71121	Glare shield · 180°
B79831	Glare shield · 360°

See individual accessory spec sheet for details.



Performance floodlights · Very narrow beam

	LED	β	A	B	C	D
B84222	61.7 W	12°	8 1/4	12 3/8	5 1/4	5 1/8

