

Application

Light building element with asymmetric wide beam light distribution. Light building elements are luminous design features for public areas. They are usually suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Extruded aluminum pole shaft
High temperature silicone gasket
Galvanized steel anchorage
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 72.8 lbs.

EPA (Effective projection area): 9.7 sq. ft.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 15.4 W
System wattage 19.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 2520 lm
LED service life (L70) 60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ RAL:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

- ☐ B71140 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- ☐ CUS Custom finish
- ☐ FSC Fusing
- ☐ MGU Marine grade undercoat
- ☐ RAL RAL Classic, matte finish

Included (available for pre-shipment)

- ☐ B79802 Buried anchorage kit



Building element · Asymmetric wide beam · Single

	LED	A	B	C
B84273	15.4 W	9 1/4	11	137 3/4

