

Application
Compact performance floodlight with mounting canopy for mounting to horizontal or vertical surfaces. Designed to spotlight architectural features, landscaping or signage. Pair with a variety of optical accessories.

Materials
Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Pure anodized aluminum reflector surface
Composite concentric ring louver
BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.2 lbs.

EPA (Effective projection area): 0.32 sq. ft.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 12.8 W
System wattage 18.0 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 518 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish

Available accessories
B71111 Glare shield · 180°
B79830 Glare shield · 360°
See individual accessory spec sheet for details.



Performance floodlights · Very narrow beam						
	LED	β	A	B	C	D
B84408	12.8 W	5°	6 ⁷ / ₈	10 ¹ / ₈	5	4

