

Application

The shielded design of this bollard provides visual comfort while illuminating ground surfaces. This asymmetric distribution is ideal for illuminating large pathways and courtyards. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass  
Extruded aluminum  
Silicone applied robotically to casting, plasma treated for increased adhesion  
Stainless steel hardware  
Stainless steel helicoils  
Threaded stainless steel anchor rods  
Mounting template included  
Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 27.1 lbs.

Electrical

Operating voltage 120-277VAC  
Minimum start temperature -30° C  
LED module wattage 11.5W  
System wattage 18.0W  
Controllability 0-10V, TRIAC, and ELV dimmable  
Color rendering index Ra > 80  
Luminaire lumens 1892lm  
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Bronze (BRZ) Black (BLK)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:



| Bollard · Asymmetric |       |                               |                                |                               |
|----------------------|-------|-------------------------------|--------------------------------|-------------------------------|
|                      | LED   | A                             | B                              | C                             |
| <b>B84463</b>        | 11.5W | 8 <sup>5</sup> / <sub>8</sub> | 38 <sup>7</sup> / <sub>8</sub> | 8 <sup>5</sup> / <sub>8</sub> |

Type:

BEGA Product:

Project:

Modified:

Available options

70896 Direct burial anchorage (replaces included anchorage kit, pre-shippable)  
CUS Custom finish  
DALI-2 Enabled for DALI control system  
EMPK Integral emergency battery pack  
FSC Fusing  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL Classic, matte finish

Included (available for pre-shipment)

B79818 Anchorage kit

