

Application

Pole-top luminaire with unshielded symmetric light distribution. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas.

Materials

White UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Stainless steel hardware
Mounting hardware included

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 13.7 lbs.

Electrical

LED module wattage	24.0 W
System wattage	28.0 W
Color rendering index	Ra > 80
Luminaire lumens	3009 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish



Pole-top luminaire · Symmetric

	LED	A	B
B84483	24.0 W	19 ⁵ / ₈	8 ⁷ / ₈

