

Application

Compact performance floodlights for use with BEGA profile poles. Designed to spotlight architectural features, landscaping or signage. Pair with a variety of optical accessories. The BEGA profile pole system is an easy way to elevate, mount, and direct up to 8 floodlights to meet any directed lighting needs.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Stainless steel hardware
- BEGA Hybrid Optics®
- Pure anodized aluminum reflector surface
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.4 lbs.

EPA (Effective projection area): 0.22 sq. ft.

Electrical

- | | |
|---------------------------|--------------------------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| LED module wattage | 18.2 W |
| System wattage | 20.0 W |
| Controllability | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1259 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---------------------------------------|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ RAL: | ☐ CUS: |

Type:

BEGA Product:

Project:

Modified:


Available options

- | | |
|---------------------------------|--|
| ☐ B71120 | Elliptical spread lens (Not compatible with internal louver) |
| ☐ CUS | Custom finish |
| ☐ MGU | Marine grade undercoat |
| ☐ RAL | RAL Classic, matte finish |

Available accessories

- | | |
|---------------------------------|---------------------|
| ☐ B71118 | Glare shield · 180° |
| ☐ B79829 | Glare shield · 360° |

See individual accessory spec sheet for details.



Profile performance floodlights · Very narrow beam

	LED	β	A	B	C
B84661	18.2 W	8°	5 ³ / ₄	8 ³ / ₄	3 ⁷ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026 Updated 06/25/26