

Application
Bollard with unshielded symmetric light distribution. Designed for landscapes, pathways, and open spaces, these robust luminaires can delineate and structure exterior spaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials
White UV-stabilized acrylic diffuser
Die-cast aluminum
Extruded aluminum
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 40.2 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	32.0 W
System wattage	39.0 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	2411 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

☐ Black (BLK)	☐ Bronze (BRZ)
☐ Silver (SLV)	☐ White (WHT)
☐ Natural Bronze (NTB)	☐ RAL:
☐ CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options

☐ 70896	Direct burial anchorage (replaces included anchorage kit, pre-shippable)
☐ CUS	Custom finish
☐ FSC	Fusing
☐ MGU	Marine grade undercoat
☐ NTB	Natural bronze (premium finish)
☐ RAL	RAL Classic, matte finish

Included (available for pre-shipment)

☐ B79818	Anchorage kit
---------------------------------	---------------



Bollard · Unshielded with safety guard			
	LED	A	B
B84668	32.0W	8 ⁵ / ₈	47 ¹ / ₄

