

Application

Bollard luminaires with shielded light distribution that are ideal for providing a high level of illuminance directly in front of the luminaire while providing exceptional glare control.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Self-expanding sleeve anchors for pre-cast concrete
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 26.7 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-40° C
- LED module wattage12.3 W
- System wattage14.5 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1100 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



Bollard · Directed light · shielded

	LED	A	B	C
B84672	12.3 W	13 3⁄8	31 1⁄2	4

