

Application

Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atriums.

Materials

- Optically textured UV-stabilized acrylic diffuser
- Die-cast aluminum
- Extruded aluminum pole shaft
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mounting hardware included
- Mounting template included
- Must be fixed to the ground
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 24.3lbs.

Electrical

LED module wattage	19.5 W
System wattage	24.0 W
Color rendering index	Ra > 80
Luminaire lumens	2358 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ RAL:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

- ☐ B71242
- ☐ CUS
- ☐ DALI-2
- ☐ FSC
- ☐ MGU
- ☐ RAL
- Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- Custom finish
- Enabled for DALI control system
- Fusing
- Marine grade undercoat
- RAL Classic, matte finish

Included (available for pre-shipment)

- ☐ B71243
- Anchorage Kit



Building element · Asymmetric

	LED	A	B	C
B84748	19.5 W	5 1/4	18 1/2	97 1/4

