

Application

Bollard with fully shielded light distribution. The glare-free illumination of these luminaires is ideally suited for lighting entrances and footpaths as well as many areas of garden and landscape architecture.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel hardware
- Self-expanding sleeve anchors for pre-cast concrete
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 8.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage7.4 W
- System wattage12.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens1010 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)Bronze (BRZ)
- Natural Bronze (NTB)Silver (SLV)
- White (WHT)RAL:
- CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- 70894Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- AMBAmber LED
- CUSCustom finish
- DALI-2Enabled for DALI control system
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



Bollard · Shielded

	LED	A	B	C
B84751	7.4 W	9 ⁷ / ₈	21 ⁵ / ₈	4 ³ / ₈

