

Application

Designed for the general illumination of trees, walls, signage and other surfaces where conventional in-grades or floodlights do not meet the requirements.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Fully potted waterstopper cable
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 5.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	20.2 W
System wattage	26.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2824 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

- ☐ Black (BLK)
 - ☐ Silver (SLV)
 - ☐ RAL:
- ☐ Bronze (BRZ)
 - ☐ White (WHT)
 - ☐ CUS:

Type:
BEGA Product:
Project:
Modified:

Available options

- ☐ B71246
 - ☐ CUS
 - ☐ DALI-2
 - ☐ FSC
 - ☐ NTB
 - ☐ RAL
- Direct burial anchorage
 - Custom finish
 - Enabled for DALI control system
 - Fusing
 - Natural bronze (premium finish)
 - RAL Classic, matte finish



On-ground luminaire · Symmetric				
	LED	β	A	B
B84757	20.2 W	28°	8	5 1/2

