

Application

Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atriums.

Materials

- White UV-stabilized acrylic diffuser
- Die-cast aluminum
- Extruded aluminum pole shaft
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Anchorage must be buried
- Galvanized steel anchorage
- Mounting hardware included
- Mounting template included

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 30.0 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage15.2 W
- System wattage20.0 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2468 lm
- LED service life (L70)60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ RAL:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ CUS:



Building element · Unshielded

	LED	A	B	C
B84894	15.2 W	5 ⁵ / ₈	18 ¹ / ₂	97 ³ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

- ☐ B71242 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- ☐ CUS Custom finish
- ☐ DALI-2 Enabled for DALI control system
- ☐ FSC Fusing
- ☐ MGU Marine grade undercoat
- ☐ RAL RAL Classic, matte finish

Included (available for pre-shipment)

- ☐ B71243 Anchorage Kit

