

Application

Pathway luminaire with shielded light for use in the private sector with a direct burial anchorage for installation in concrete or soil. These luminaires are ideally suited for garden, entryways, and for many applications on paths and terraces. 24V DC transformer required for operation.

Materials

Clear safety glass with matte finish
Aluminum housing
High temperature silicone gasket
Stainless steel hardware
Stainless steel helicoils
Silicone applied robotically to casting, plasma treated for increased adhesion
Anchorage must be buried

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 9.3 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-20° C
LED module wattage	3.9W
System wattage	5.0W
Controllability	DALI-2
Color rendering index	Ra > 80
Luminaire lumens	236lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Natural Bronze (NTB)	Silver (SLV)
White (WHT)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:


Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Available accessories

B19580	Remote driver box · Static white
B19591	Remote driver box · Static white

See individual accessory spec sheet for details.



Garden bollard · Direct burial anchorage · 24V DC

	LED	A	B
B85178	3.9W	37 ⁷ / ₈	27 ⁵ / ₈

