

Application
Pathway luminaire with shielded light for use in the private sector. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Hardscape base is intended for installation on foundations or paved surfaces. 24V DC transformer required for operation.

Materials
Clear safety glass with matte finish
Aluminum housing
High temperature silicone gasket
Silicone applied robotically to casting, plasma treated for increased adhesion
Stainless steel hardware
Stainless steel helicoils
Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 7.5 lbs.

Electrical
Operating voltage 24VDC (remote power supply req.)
Minimum start temperature -20° C
LED module wattage 5.0W
System wattage 7.0W
Controllability DALI-2
Color rendering index Ra > 80
Luminaire lumens 257 lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Natural Bronze (NTB) White (WHT)
Silver (SLV) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available accessories
B19580 Remote driver box · Static white
B19591 Remote driver box · Static white
See individual accessory spec sheet for details.



Garden bollard · Hardscape base · 24V DC			
	LED	A	B
B85183	5.0W	37 ⁵ / ₈	27 ⁵ / ₈

