

Application

Pathway luminaire with shielded light for use in the private sector with a direct burial anchorage for installation in concrete or soil. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Luminaires are specified in one paint finish for the bollard body; the interior is finished in Natural Bronze as standard. 24V DC transformer required for operation.

Materials

- Clear safety glass with matte finish
- Aluminum housing
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Stainless steel hardware
- Stainless steel helicoils
- Anchorage must be buried

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 8.6 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-20° C
LED module wattage	5.0W
System wattage	7.0W
Controllability	DALI-2
Color rendering index	Ra > 80
Luminaire lumens	268lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:



Garden bollard · Direct burial anchorage · 24V DC

	LED	A	B
B85184	5.0W	37 ⁵ / ₈	27 ⁵ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish

Available accessories

B19580	Remote driver box · Static white
B19591	Remote driver box · Static white

See individual accessory spec sheet for details.

