

Application

Pole-top luminaires with asymmetrical light distribution. The asymmetrical light distribution is ideal for illuminating parking areas, roadways and walkways. Luminaire includes DALI standard with Zhaga interface and optional BEGA Connect capability. DarkSky Approved (2700K and 3000K only).

Materials

Optically textured UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mounting hardware included
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.1 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -40° C
LED module wattage 37.0 W
System wattage 44.0 W
Controllability DALI D4i
Color rendering index Ra > 80
Luminaire lumens 3622 lm
LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3) (DarkSky Approved)
- 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:

Modified:


Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL Classic, matte finish

Available accessories

- B71210 Air Connector · Zhaga Book 18 Ed 3.0

See individual accessory spec sheet for details.



Pole-top luminaire · Asymmetric with Zhaga Receptacle

	LED	A	B
B85198	37.0W	13	15 ³ / ₈

