

Application

Pole-top luminaire with a clear globe-shaped diffuser, opaque top shield, and symmetric light distribution for the illumination of pedestrian spaces such as plazas, walkways, and building entrances.

Materials

Clear UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Stainless steel hardware
Mechanically captive stainless steel fasteners
Mounting hardware included
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 12.4 lbs.

Electrical

Operating voltage 120V or 277V AC
Minimum start temperature -10° C
LED module wattage 37.5 W
System wattage 43.0 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 2774 lm
LED service life (L70) 60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)
- ☐ RAL:
- ☐ CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ CUS
- Custom finish
- ☐ DALI-2
- Enabled for DALI control system via DALI-2 to 0-10V translator with relay. One way communication only.
- ☐ FSC
- Fusing
- ☐ MGU
- Marine grade undercoat
- ☐ NTB
- Natural bronze (premium finish)
- ☐ RAL
- RAL Classic, matte finish



Pole-top luminaire · Symmetric			
	LED	A	B
B85221	37.5 W	18	20 ^{5/8}