

Application
Bollard with 360° light distribution in stainless steel. This luminaire is designed to illuminate paths, entrances and driveways in private and public areas.

Materials
Chemically hardened soda-lime glass
Corrosion-resistant 304 grade stainless steel
Zinc plated carbon steel anchor bolts with template
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 26.5 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	7.9W
System wattage	11.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	766lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Included (available for pre-shipment)
B79818 Anchorage kit



Bollard · Shielded with reflector · 360°				
	LED	A	B	C
B88060	7.9W	6 ¹ / ₈	36 ⁷ / ₈	9 ¹ / ₂