

Application

Bollard with adjustable light distribution. Adjust internal optics to 0°, 15° or 30° angle in either direction for a variety of distribution options with a single luminaire. Designed for effective lighting of landscapes, pathways, and open spaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Clear safety glass
- A380 aluminum alloy
- High temperature silicone gasket
- Zinc plated carbon steel anchor bolts with template
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 28.7 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage17.9 W
- System wattage30.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 90
- Luminaire lumens1236 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:

BEGA Product:

Project:


Modified:

Available options

- | | |
|-------|--|
| 70895 | Direct burial anchorage (replaces included anchorage kit, pre-shippable) |
| CUS | Custom finish |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish |

Included (available for pre-shipment)

- | | |
|--------|---------------|
| B79817 | Anchorage kit |
|--------|---------------|



Bollard · Adjustable

	LED	A	B	C
B88062	17.9 W	10 ⁵ / ₈	43 ³ / ₈	5 ¹ / ₂

