

Application

Bollard with shielded light distribution. Designed for effective lighting of landscapes, pathways, and open spaces from low mounting heights. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass
A380 aluminum alloy
High temperature silicone gasket
Zinc plated carbon steel anchor bolts with template
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 20.3lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 7.9W
System wattage 12.0W
Controllability 0-10V dimmable
Color rendering index Ra > 90
Luminaire lumens 551 lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

70895 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish

Included (available for pre-shipment)

B79817 Anchorage kit



Bollard · Symmetric

	LED	A	B	C
B88066	7.9W	10 ⁵ / ₈	23 ³ / ₄	5 ¹ / ₂

