

Application
Pole-top luminaire with symmetric light distribution and shallow height. The uniform distribution is ideal for illuminating squares, plazas and other open areas.

Materials
White UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 13.2 lbs.

EPA (Effective projection area): 0.7 sq. ft.

Electrical	
Operating voltage	120, 220-240 OR 277 VAC
Minimum start temperature	-30° C
LED module wattage	25.2 W
System wattage	30.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2531 lm
LED service life (L70)	60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish



Pole-top luminaire · Symmetric		
	LED	A B
B88164	25.2 W	24 1/4 5 1/2

