

Application
Pole-top luminaire with symmetric light distribution and shallow height. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas.

Materials
White high-density polyethylene diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 25.5 lbs.
EPA (Effective projection area): 1.0 sq. ft.

Electrical
Operating voltage 120, 220-240 OR 277 VAC
Minimum start temperature -30° C
LED module wattage 16.0W
System wattage 19.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1809lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
RAL RAL Classic, matte finish



Pole-top luminaire · Symmetric			
	LED	A	B
B88260	16.0W	27 1/2	12 5/8