

Application

Factory sealed recessed wall luminaire designed to be installed in walls or other vertical or horizontal surfaces for both interior and exterior locations.

Materials

- Clear safety glass with white ceramic coating
- Corrosion-resistant 304 grade stainless steel
- Stainless steel screw clamps
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 1.3 lbs.

Electrical

LED module wattage	0.1 W
System wattage	1.0 W
Color rendering index	Ra > 80
Luminaire lumens	2 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available accessories

- ☐ B19580 Remote driver box · Static white
- ☐ B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- ☐ BB8300LED Installation housing



Recessed wall luminaire · Location luminaire · 24V DC					
		LED	A	B	C
B88300	ADA	0.1 W	4	1½	2¾

