

Application

Factory sealed recessed wall luminaire designed to be installed in walls or other vertical or horizontal surfaces for both interior and exterior locations.

Materials

- Clear safety glass with white ceramic coating
- Corrosion-resistant 304 grade stainless steel
- Stainless steel screw clamps
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 67

Weight: 11.9lbs.

Electrical

|                        |           |
|------------------------|-----------|
| LED module wattage     | 1.9W      |
| System wattage         | 3.0W      |
| Color rendering index  | Ra > 80   |
| Luminaire lumens       | 32 lm     |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available accessories

- B19580 Remote driver box · Static white
- B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- BB7002LED Installation housing



| Recessed wall luminaire · Location luminaire · 24V DC |     |      |                                |                               |   |
|-------------------------------------------------------|-----|------|--------------------------------|-------------------------------|---|
|                                                       |     | LED  | A                              | B                             | C |
| B88303                                                | ADA | 1.9W | 39 <sup>3</sup> / <sub>8</sub> | 2 <sup>1</sup> / <sub>8</sub> | 4 |

