

Application

A ground mounted luminaire with low mounting height and 180° light distribution. The narrow beam light distribution is ideally suited for illuminating and grazing ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Chemically hardended soda-lime glass
A380 aluminum alloy
High temperature silicone gasket
Glass collimator

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 6.0 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 9.0W
System wattage 12.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 145lm
LED service life (L70) 60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ Natural Bronze (NTB)
- ☐ CUS:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- ☐ CUS Custom finish
- ☐ FSC Fusing
- ☐ MGU Marine grade undercoat
- ☐ RAL RAL Classic, matte finish

Included (available for pre-shipment)

- ☐ B79815 Anchorage kit



On-ground luminaire · 180° light output			
	LED	A	B
B88360	9.0W	6 ³ / ₄	7 ¹ / ₂

