

Application

BEGA system bollard luminaire tube without components. BEGA system bollard tubes are designed for easy attachment to system bollard heads using an interlocking mechanism. An accompanying bollard head must be selected for proper installation.

Materials

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Extruded aluminum
Interlocking stainless steel mounting mechanism for attachment of head and tube
Stainless steel hardware
Stainless steel helicoils
Threaded stainless steel anchor rods

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 24.5 lbs.

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options

70896	Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

B79818	Anchorage kit
--------	---------------



	A	B
B96178	10 ³ / ₈	34 ¹ / ₂



System bollard summary · Round

BEGA

The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

System bollard heads with compatible tubes																					
BEGA bollard tubes Ø in inches		ø5 1/2	ø7 1/2	ø5 1/2	ø7 1/2	ø10 3/8	ø5 1/2	ø7 1/2	ø5 1/2	ø7 1/2	ø7 1/2	ø7 1/2	ø10 3/8	ø7 1/2	ø10 3/8	ø7 1/2	ø5 1/2	ø7 1/2	ø10 3/8		
	Without components in two heights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
	With integral floodlight		•		•			•		•	•	•			•			•			
	With integral PIR motion sensor		•		•	•		•		•	•	•	•	•	•	•		•	•		
	With emergency lighting battery		•		•	•		•		•	•	•	•	•	•	•		•	•		
	With drive-through protection					•								•							
	With integral GFCI outlet		•		•	•		•		•	•	•	•	•	•	•		•	•		
	With integral 240V receptacle for electric vehicles					•								•							
	Wood bollard tubes	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		

Compatible heads · Ø10 3/8

System bollard head · Unshielded with safety guard · 180°

	LED	A	B
B99778	29.4 W	10 3/8	8 7/8

System bollard head · Unshielded with safety guard · 360°

	LED	A	B
B99777	29.4 W	10 3/8	8 7/8

System bollard head · Shielded · 360°

	LED	A	B
B99865	29.4 W	10 3/8	7 5/8

System bollard head · Non-illuminated cap

	A	B
B71128	10 3/8	0 3/4

System bollard head · 180° light output

	LED	A	B
B84707	11.6 W	10 3/8	3 7/8

System bollard head · 360° light output

	LED	A	B
B84705	23.6 W	10 3/8	3 7/8