

Application

Designed for the general illumination of trees, walls, signage and other surfaces where conventional in-grades or floodlights do not meet the requirements.

Materials

Clear safety glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 67

Weight: 18.0lbs.

Electrical

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277VAC     |
| Minimum start temperature | -30° C         |
| LED module wattage        | 7.9W           |
| System wattage            | 11.0W          |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 596lm          |
| LED service life (L70)    | 60000hrs       |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:


BEGA Product:

Project:

Modified:

Available options

|     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| ESL | Elliptical spread lens          |
| FSC | Fusing                          |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish       |



Ground mounted floodlight · Adjustable

|        | LED  | β   | A | B                             | C                              |
|--------|------|-----|---|-------------------------------|--------------------------------|
| B98006 | 7.9W | 12° | 9 | 9 <sup>3</sup> / <sub>4</sub> | 11 <sup>3</sup> / <sub>4</sub> |

