Type:
BEGA Product:
Project:
Modified:

Application
BEGA Furniture partitions are designed to delineate space while maintaining a timeless, cohesive design. The integral illumination is intended to add effective lighting for wayfinding in various outdoor settings. Provided with signage complete with individual lettering, symbols, or logos, consult factory for details.

Materials
Clear safety glass with white ceramic coating
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
Zinc plated carbon steel anchor bolts with template

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 127.9 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	47.2 W
System wattage	55.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	3661 lm
LED service life (L70)	60000 hrs

LED color temperature
☐ 4000K (K4)
☐ 3500K (K35)
☐ 3000K (K3)
☐ 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
☐ Black (BLK)
☐ Silver (SLV)
☐ RAL:
☐ Bronze (BRZ)
☐ White (WHT)
☐ CUS:

Available options

☐ CUS	Custom finish
☐ FSC	Fusing
☐ MGU	Marine grade undercoat
☐ RAL	RAL Classic, matte finish





<<multiple values>> · With signage

	LED	A	B	C	D
B99069	47.2 W	69	39 3/8	23 1/4	7

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026