

Application

Unshielded light is ideally suited for the illumination of pathways, entrance areas, or in a garden or residential area. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass with white ceramic coating
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Silicone applied robotically to casting, plasma treated for increased adhesion
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 17.6lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -20° C
LED module wattage 22.8W
System wattage 32.0W
Controllability 0-10V dimming down to 0.1%
Color rendering index Ra > 80
Luminaire lumens 1432lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

70895 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS Custom finish
DALI-2 Enabled for DALI control system
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish

Included (available for pre-shipment)

B79817 Anchorage kit



Bollard · Light emission on two sides				
	LED	A	B	C
B99330	22.8W	4 ³ / ₄	39 ³ / ₈	3 ¹ / ₈

