

Application

Pole-top luminaire with asymmetric wide beam light distribution ideal for illuminating roads and pathways.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 20.0lbs.

EPA (Effective projection area): 0.8 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage23.6W
- System wattage28.0W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens3117 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Bronze (BRZ)
- Silver (SLV)
- White (WHT)
- RAL:
- CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- RALRAL Classic, matte finish



Pole-top luminaire · Asymmetric wide beam · Single

	LED	A	B	C
B99407	23.6W	18 ⁷ / ₈	2 ¹ / ₄	24

