

Application

Davit arm luminaire with asymmetric wide beam light distribution designed for the illumination of parking areas and roadways. Tool-less entry with hinged door for ease of maintenance. Slip fits 1 5/8" O.D. tenon, secures to pole with integrated slip fitter mechanism and lateral set screws.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 11.0 lbs.

EPA (Effective projection area): 0.3 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage31.4 W
- System wattage35.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens4555 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Area/Roadway luminaire · Asymmetric wide beam

	LED	A	B	C
B99433	31.4 W	10	2 ³ / ₈	19 ¹ / ₄

Type:

BEGA Product:

Project:

Modified:

Available options

- 347V347V input
- AMBAmber LED
- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- RALRAL Classic, matte finish

