

Application

Bollard luminaire with shielded light distribution that is ideal for providing a high level of illuminance directly in front of the luminaire while providing exceptional glare control. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Self-expanding sleeve anchors for pre-cast concrete
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 8.8lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	6.3W
System wattage	9.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	444lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

- ☐ Black (BLK)
 - ☐ Silver (SLV)
 - ☐ Natural Bronze (NTB)
 - ☐ CUS:
- ☐ Bronze (BRZ)
 - ☐ White (WHT)
 - ☐ RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- ☐ CUS
 - ☐ MGU
 - ☐ NTB
 - ☐ RAL
- Custom finish
 - Marine grade undercoat
 - Natural bronze (premium finish)
 - RAL Classic, matte finish



Bollard · Directed light · asymmetric				
	LED	A	B	C
B99554	6.3W	6 ³ / ₈	31 ¹ / ₂	4 ³ / ₈

