

Application

Bollard luminaire with shielded light distribution that is ideal for providing a high level of illuminance directly in front of the luminaire while providing exceptional glare control. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Self-expanding sleeve anchors for pre-cast concrete
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 22.0lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- Maximum ambient temperature90° C
- LED module wattage17.6W
- System wattage30.0W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 90
- Luminaire lumens1662lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- CUSCustom finish
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish

Included (available for pre-shipment)

- B79817Anchorage kit



Bollard · Directed light · asymmetric				
	LED	A	B	C
B99558	17.6W	9 ⁷ / ₈	43 ³ / ₈	5 ¹ / ₂

