

Application

Bollard with shielded 360° light distribution. This luminaire is designed to provide rotationally symmetric illumination of ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Borosilicate glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 26.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage12.4 W
- System wattage15.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens451 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- RALRAL Classic, matte finish

Included (available for pre-shipment)

- B79818Anchorage kit



Bollard · 360° light output			
	LED	A	B
B99578	12.4 W	11 7/8	19 3/4

