Type:
BEGA Product:
Project:
Modified:

Application
BEGA system bollard head with shielded 360° light distribution. Simply order the bollard head and also the required bollard tube in various heights and options. Both modules can be joined together easily and quickly during the installation.

Materials
Clear safety glass
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Interlocking stainless steel mounting mechanism for attachment of head and tube
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.3 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	6.0 W
System wattage	10.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	664 lm
LED service life (L70)	60000 hrs

LED color temperature
☐ 4000K (K4)
☐ 3500K (K35)
☐ 3000K (K3)
☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
☐ Black (BLK)
☐ Bronze (BRZ)
☐ Silver (SLV)
☐ White (WHT)
☐ Natural Bronze (NTB)
☐ RAL:
☐ CUS:

Available options

☐ CUS	Custom finish
☐ MGU	Marine grade undercoat
☐ NTB	Natural bronze (premium finish)
☐ RAL	RAL Classic, matte finish





System bollard head · Symmetric · 360°

	LED	A	B
B99852	6.0 W	5 1/2	5 1/2

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026

System bollard summary · Round

BEGA

The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

System bollard heads with compatible tubes									
BEGA bollard tubes Ø in inches	ø5½	ø7½	ø5½	ø7½	ø10⅜	ø5½	ø7½	ø5½	ø7½	ø7½	ø7½	ø10⅜	ø7½	ø10⅜	ø7½	ø5½	ø7½	ø10⅜
 Without components in two heights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 With integral floodlight		•		•			•		•	•	•		•		•		•	
 With integral PIR motion sensor		•		•	•		•		•	•	•	•	•	•	•		•	•
 With emergency lighting battery		•		•	•		•		•	•	•	•	•	•	•		•	•
 With drive-through protection					•							•		•				•
 With integral GFCI outlet		•		•	•		•		•	•	•	•	•	•	•		•	•
 With integral 240V receptaclefor electric vehicles					•							•		•				•
 Wood bollard tubes	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Compatible tubes · Ø5½

System bollard tube · No access door

	A	B
B99614	5½	14¼

System bollard tube · No access door

	A	B
B99620	5½	26

Wood system bollard tube · Round

	A	B
B84476	5½	25⅞

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026

Updated 06/25/26