

Application
Twin pole-top luminaire with asymmetric light distribution. These luminaires provide light in front of the luminaire to uniformly wash surfaces for plazas and parking lots.

Materials
Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Galvanized steel anchorage
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 42.8lbs.

EPA (Effective projection area): 1.5 sq. ft.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 31.2W
System wattage 36.0W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 4052lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
DALI-2 Enabled for DALI control system
MGU Marine grade undercoat
RAL RAL Classic, matte finish

Included (available for pre-shipment)
722-XXX Pole assembly



Adjustable luminaire with pole · Asymmetric · Twin				
	LED	A	B	C
B99869	31.2W	10 ¹ / ₄	98 ¹ / ₂	25 ¹ / ₄