

Application
Pole-top luminaire with asymmetric wide beam light distribution. These luminaires are ideally suited for illuminating roads and pathways.

Materials
Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Galvanized steel anchorage
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 8.8 lbs.

EPA (Effective projection area): 0.8 sq. ft.

Electrical	
Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	15.8 W
System wattage	20.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	2172 lm
LED service life (L70)	60000 hrs

- LED color temperature**
- 4000K (K4)
 - 3500K (K35)
 - 3000K (K3)
 - 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
DALI-2	Enabled for DALI control system
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish

Included (available for pre-shipment)	
722-XXX	Pole assembly



Adjustable luminaire with pole · Asymmetric wide beam · Single				
	LED	A	B	C
B99878	15.8 W	10 1/4	98 1/2	12 1/2